

DRILLMAX[®]

Manufacturer of Geothermal & Water Well Rigs

MAX 350 | Standard Specifications



For further details and pricing please contact:
Donnie Wood, DRILLMAX[®]
 800-457-3737 or 352-427-7787
 5801 SW 6th Place • Ocala, FL 34474

SUB FRAME

- Construction..... 15 ft. in length
- Component supporting sub frame with aluminum cover plates to minimize weight and deter corrosion.

MAST

- Construction.....29 ft. 6 in. length
- With internal cylinder and sealed bearing hoisting system.
- Integral table provides 12 in. opening.

DRILL POWER

- PTO driven by heavy-duty oil flooded pump drive gear case with direct coupling to all hydraulic pumps.

HYDRAULIC SYSTEM

- Independent systems for each main circuit allowing for continuous drilling operations while handling drill pipe.
- Includes 85 gal. hydraulic tank with oil cooler and filtration.

FEED SYSTEM

- Type..... Hydraulic cylinder with leaf chain drive
- Stroke..... 24 ft.
- Rated Pullback..... 15,000 lbs.
- Rated Pulldown Pressure 10,000 lbs.

ROTARY HEAD

- Type..... Top drive oil flooded gearbox with integral 2 in. adjustable swivel
- Speed..... Available up to 300 RPM
- Torque..... Available up to 48,000 in-lbs.

STANDARD PIPE HANDLING EQUIPMENT

- Holding wrench..... Air Operated
- Breakout Cylinder..... Hydraulic cylinder with 36 in. adjustable wrench
- Winch..... 7,500 lbs. capacity with 100 ft. x 1/2 in. non-rotating wire rope and safety hook
- JIB Boom Hydraulically swings and extends to center over pipe rack loader

LEVELING JACKS

- Rear..... Two 30 in. stroke
- Front..... Two 36 in. stroke

TRUCK CHASSIS

- Ford F-750, H.P. Diesel with 6 Speed transmission, 4x4 conversion available
- International 7300 4x4

WEIGHT

- Approximate operating weight 30,000 lbs.

DIMENSIONS

- Length..... 30 ft.
- Width..... 8 ft.
- Height 10 ft. 6 in.

OPTIONAL EQUIPMENT

- Mud Pump: Hydrastatic driven up to 5 x 6 Duplex or 3 x 4 x 13 Centrifugal
- Air Compressor: Hydrastatic driven 300 CFM at 200 PSI Piston
**When used with Duplex Pump*
- Drill Pipe Rack for 300 ft. of 2 7/8 in. x 20 ft.
- CMAX Semi-Automatic drill pipe loading system with up to 15 pieces (300 ft) 2 7/8 in. drill pipe